KRAUSE

Ladders and scaffold systems

NEW

STABILO® Professional

Telescopic platform ladder SkyMatic

www.krause-systems.com

QUALITY Since 1900

STABILO® Professional

Telescopic platform ladder SkyMatic

Single-sided, mobile telescopic platform ladder with large platform and all-round platform railing. Safe and comfortable working combined with quick and easy handling.

+ Mobile, height-adjustable aluminium platform ladder according to DIN EN 131-7, single-sided access, with large platform incl. 4-sided platform guardrail for safe and comfortable working
+ Convenient and easy handling – all guardrails and the transition barrier are automatically positioned when the ladder is unfolded
+ Working heights of 2.80 m – 3.30 m can be achieved with the 1 x 3 to 1 x 5 rung version and working heights of 3.30 m – 4.35 m with the 1 x 5 to 1 x 9 version
+ Maximum flexibility and use on stairs and landings thanks to height adjustment from rung to rung on both sides
+ Comfortable and smooth height adjustment thanks to patented ClickMatic-System
+ All-round safe workplace in accordance with TRBS 2121-2 thanks to three-sided platform railing and self-closing transition barrier
+ Platform size 600 x 500 mm made of slip-resistant aluminium profile
+ Smooth-running quick-release fastener on the platform provides additional stability and prevents the ladder from folding up unintentionally
+ 150 mm high toeboard for increased safety (**200 % higher** than required by the EN 131-7 standard)
+ Sturdy flanged rung/rail connection with flush transition to the platform
+ Two stable stabilisers with slip-resistant foot caps (SafetyCap)
+ Easy and convenient to move with one hand thanks to two fixed castors integrated into the stabiliser
+ Small stand width, ideal for working close to objects
+ With art.-no. 832948, infinitely adjustable outriggers on both sides ensure even greater stability. From version 1 x 7 rungs the stabilisers must be used
+ Space-saving storage thanks to compact folding dimensions – fixing straps prevent unintentional unfolding
+ Supplied with a suitable Velcro tool bag that can be used anywhere thanks to a removable shoulder strap
+ Pre-equipped with a wosatec QR code label for easy digitalisation of work equipment inspection documentation

TÜV SÜD · Certificate EN 131-7 Norm · TRBS 2121-2:2015 · Workplace

STABILO® Professional

Installation variants:

1 x 3	1 x 4	1 x 5
832924		

Can be used on stairs and landings thanks to height adjustment on both sides in all variants.

1 x 5	1 x 6	1 x 7	1 x 8	1 x 9
832948				

Technical data:

Number of rungs incl. platform				3	4	5	5	6	7	8	9
1		**A** up to approx.	m	2.80	3.05	3.30	3.30	3.60	3.85	4.10	4.35
		B approx.	m	0.80	1.05	1.30	1.30	1.60	1.85	2.10	2.35
2		**C** approx.	m	2.00	2.30	2.60	2.60	2.90	3.20	3.45	3.70
		D approx.	m	1.90	2.20	2.45	2.45	2.70	3.00	3.20	3.50
Stabiliser width approx.			m	0.90			0.90				
Floor area B x L approx.			m	0.90 x 1.10	0.90 x 1.30	0.90 x 1.45	0.90 x 1.45	0.90 x 1.65	1.70 x 1.80	1.70 x 2.00	1.70 x 2.20
Product weight approx.			kg	30.0			40.0				
		Width (B) approx.	m	0.90			0.90				
		Depth (T) approx.	m	0.50			0.50				
		Length (L) approx.	m	2.25			2.80				
Art.-No.				832924			832948				

The highlights...

All-round safe workplace thanks to 3-sided railing cage and self-closing transition barrier



600 x 500 mm large, slip-resistant aluminium platform



Extra high toeboard – with **150 mm** height **200 % higher** than the standard

Space-saving storage: Separate strap secures against unintentional unfolding

Incl. Velcro tool bag with detachable shoulder strap

Quick-release fastener for additional stability and against unintentional folding

Comfortable, smooth-running height adjustment thanks to the patented ClickMatic-System

Easy to move thanks to integrated castors



Steplessly adjustable outriggers (art.-no. 832948)

© 2024 by KRAUSE-Werk D-36304 Alsfeld.
Subject to technical modifications, printing errors and mistakes; in cases of doubt, the original German text should be consulted. The specified dimensions and weights have been determined on the basis of the technical drawings; the actual dimensions and weights may deviate due to tolerances and rounding. None of the accessories, EXTRAS or work equipment shown are included in the scope of supply. No liability shall be accepted for improper use. Only use genuine KRAUSE replacement parts.